



Service Bulletin

SB

Distribution
EXPORT

Product
Valtra tractors

Group
40

Regarding
XT 60 OIL IN TRANSMISSION

No
074

Issued by
LSa

Date
922

Sheet
1(1)

Valtra XT 60 is a transmission oil that was developed to meet the requirements of the new Versu and Direct transmissions. XT 60 is recommended for use in other Valtra transmissions as well, including the new and old S series.

In production, XT60 oil has been used in transmissions from chassis number V11xxx- onwards.

XT 60 is yellow and can therefore be differentiated from the red HT 60 oil.

XT 60 and HT 60 can be mixed if, for example, a refill is needed and XT 60 is not available.



The image shows a technical sheet for Valtra XT60 Transmission Oil. It features a red vertical bar with the 'VALTRA' logo on the left. The top right of the sheet has a red tractor engine and a red oil can. The main title is 'Transmission XT60'. Below the title, it lists 'SAE 80W API GL-4 Valtra G2-08' and provides translations for 'Transmission and hydraulic oil' in multiple languages: Valtra-tse-hydrauliikki, Huilo beta de viasese et hidraulice, Geteele-und Hydrauliik, and Transmissiões e hidraulice. The sheet contains several columns of small text providing detailed technical specifications and usage instructions.

Classifications

- Valtra G2-08
- API GL-4

Typical characteristics

	XT 60
• Density @ 15 °C (kg/dm ³)	0,877
• Flash point (°C)	204
• Viscosity @ 40 °C (cSt)	60,1
• Viscosity @ 100 °C (cSt)	9,4
• Viscosity index (VI)	140
• Pour point (°C)	-42

This is technical information and does not constitute a warranty claim.